

**BEST AVAILABLE COPY**Listing of ClaimsRECEIVED  
CENTRAL FAX CENTER

NOV 09 2006

1. (Previously Presented) A computing device, comprising:  
an illuminable housing capable of being illuminated by light, the housing being configured to enclose internal components associated with the operation of the computing device; and  
a controllable light emitting device disposed inside the illuminable housing, the light emitting device being configured to produce an adjustable light effect for colorizing or patternizing the illuminable housing in order to significantly alter the ornamental appearance of the housing of the computing device, the light emitting device including a light source configured to generate the light so as to illuminate the interior of the illuminable housing, the light illuminating an inner surface of a housing wall to effect an appearance change in an outer surface of the housing wall.
2. (Cancelled)
3. (Cancelled)
4. (Previously Presented) The computing device as recited in claim 1 wherein the light source includes at least one light emitting diode.
5. (Previously Presented) The computing device as recited in claim 1 wherein the light source includes a plurality of light emitting diodes.
6. (Original) The computing device as recited in claim 5 wherein each of the light emitting diodes generate the same color of light.
7. (Original) The computing device as recited in claim 5 wherein each of the light emitting diodes generate individually different colors of light.
8. (Original) The computing device as recited in claim 7 wherein the light emitting diodes cooperate to produce a light effect having a single color.

**BEST AVAILABLE COPY**

9. (Original) The computing device as recited in claim 7 wherein the light emitting diodes cooperate to produce a light effect having a plurality of colors.
10. (Original) The computing device as recited in claim 5 wherein the plurality of light emitting diodes are integrated into a light emitting diode array.
11. (Original) The computing device as recited in claim 10 wherein the light emitting diode array includes a blue, red and green light emitting diode.
12. (Cancelled)
13. (Previously Presented) A computing device, comprising:  
an illuminable housing capable of being illuminated by light, the housing being configured to enclose internal components associated with the operation of the computing device; and  
a controllable light emitting device disposed inside the illuminable housing, the light emitting device being configured to produce an adjustable light effect for colorizing or patternizing the illuminable housing in order to significantly alter the ornamental appearance of the housing of the computing device, the light emitting device including a light source configured to generate the light so as to illuminate the interior of the illuminable housing, the light illuminating an inner edge of a housing wall to effect an appearance change in an outer edge of the housing wall.
14. (Previously Presented) The computing device as recited in claim 1 further including a shaped wall disposed between the light source and the housing wall, and wherein the light from the light source illuminates an inner surface of the shaped wall to produce a shaped light effect at an outer surface of the shaped wall.
15. (Previously Presented) The computing device as recited in claim 1 further including a light pipe for distributing the light to locations within the illuminable housing.
16. (Previously Presented) The computing device as recited in claim 1 further including a light guide for focusing the light generated by the light source.

**BEST AVAILABLE COPY**

17. (Previously Presented) The computing device as recited in claim 1 further including a lens for focusing the light generated by the light source.
18. (Previously Presented) The computing device as recited in claim 1 further including a reflector for redirecting the light to locations within the illuminable housing.
19. (Previously Presented) The computing device as recited in claim 1 wherein the light emitting device further comprises a light source controller in communication with the light source, said light source controller being configured to process light commands to produce the light in a controlled manner via the light source.
20. (Original) The computing device as recited in claim 1 wherein the housing wall is capable of producing a characteristic glow at the outer periphery of the housing wall when the light is transmitted through the housing wall.
21. (Cancelled)
22. (Previously Presented) The computer system as recited in claim 1 wherein the illuminable housing is configured to cover and protect the internal components.
23. (Previously Presented) The computing device as recited in claim 1 wherein the internal components comprise a processor.
24. (Previously Presented) The computing device as recited in claim 1 wherein the internal components comprise a display controller, input controller or output controller.
25. (Previously Presented) The computing device as recited in claim 1 wherein the internal components comprise a display that is distinctly separate from the light emitting device.
26. (Previously Presented) The computing device as recited in claim 1 wherein the internal components comprise an input or output device.
27. (Original) The computing device as recited in claim 1 wherein the light effect is static.

**BEST AVAILABLE COPY**

28. (Original) The computing device as recited in claim 1 wherein the light effect is dynamic.
29. (Currently Amended) A general purpose computer, comprising:  
an illuminable housing capable of being illuminated by light; and  
a controllable light emitting device disposed inside and in optical communication with  
the illuminable housing, the light emitting device being configured to produce an adjustable light effect that provides illumination for colorizing or patternizing the illuminable housing in order to significantly alter the ornamental appearance of the housing of the general purpose computer.
30. (Original) The computing device as recited in claim 29 wherein the general purpose computer is a desktop computer.
31. (Original) The computing device as recited in claim 29 wherein the general purpose computer is a laptop computer.
32. (Cancelled)
33. (Cancelled)
34. (Cancelled)
35. (Cancelled)
36. (Previously Presented) A computer system having a housing for enclosing at least one component of the computer system, the housing having a light passing wall, the computer system comprising:  
a light source disposed inside the housing, the light source being configured to generate light;  
a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall; and

**BEST AVAILABLE COPY**

a processor configured to carry out operations associated with the computer system, the processor being operatively coupled to the light source controller.

37. (Original) The computer system as recited in claim 36 wherein the processor is disposed inside the housing.

38. (Currently Amended) A computer system having a housing for enclosing at least one component of the computer system, the housing having a light passing wall, the computer system comprising:

a light source disposed inside the housing, the light source being configured to generate light for the computer system;

a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall;

a display that is internally or externally positioned relative to the housing, the display being configured to present text or graphics for the computer system; and

a display controller operatively coupled to the display and configured to process display commands to produce text or graphics on the display.

39. (Original) The computer system as recited in claim 38 wherein the display is disposed inside the housing.

40. (Original) The computer system as recited in claim 38 wherein the display controller is disposed inside the housing.

41. (Previously Presented) A computer system having a housing for enclosing at least one component of the computer system, the housing having a light passing wall, the computer system comprising:

a light source disposed inside the housing, the light source being configured to generate light;

a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing

**BEST AVAILABLE COPY**

wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall; and

an input/output controller configured to control interactions with one or more input/output devices that can be operatively coupled to the computer system.

42. (Original) The computer system as recited in claim 41 wherein the input/output controller is disposed inside the housing.

43. (Previously Presented) A computer system having a housing for enclosing at least one component of the computer system, the housing having a light passing wall, the computer system comprising:

a light source disposed inside the housing, the light source being configured to generate light;

a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall;

a processor configured to carry out operations associated with the computer system, the processor being operatively coupled to the light source controller;

a display;

a display controller operatively coupled to the processor and the display, the display controller being configured to process display commands to produce text or graphics on the display; and

an input/output controller operatively coupled to the processor, the input/output controller being configured to control interactions with one or more input/output devices that can be operatively coupled to the computer system.

44. (Original) The computer system as recited in claim 43 wherein housing is configured to enclose the light source controller, the processor, the display, the display controller, the input/output controller and at least one input/output device.

45. (Original) The computer system as recited in claim 43 wherein housing is configured to enclose the light source controller, the processor, the display controller and the input/output controller.



**BEST AVAILABLE COPY**

46. (Original) The computer system as recited in claim 43 wherein housing is configured to enclose the display.

47. (Original) The computer system as recited in claim 43 wherein housing is configured to enclose at least one input/output device.

48. (Previously Presented) A computer system having a first housing for enclosing at least one component of the computer system, and a second housing for enclosing a second component of the computer system, the first housing having a first light passing wall, the second housing having a second light passing wall, the computer system comprising:

a light source disposed inside the housing, the light source being configured to generate light;

a second light source disposed inside the second housing, the second light source being configured to generate light; and

a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall.

49. (Original) The computer system as recited in claim 48 wherein the light controller operatively coupled to the second light source, the light source controller being configured to control the second light source so as to illuminate at least a portion of the second light passing wall of the housing with the light generated by the second light source.

50. (Original) The computer system as recited in claim 48 wherein the first housing is configured to enclose a light source controller, a processor, a display controller, an input/output device controller, and wherein the second housing is configured to enclose a display.

51. (Previously Presented) A computer system having a housing for enclosing at least one component of the computer system, the housing having a light passing wall, the computer system comprising:

a light source disposed inside the housing, the light source being configured to generate light; and

APL1P215/P2698

**BEST AVAILABLE COPY**

a light controller operatively coupled to the light source, the light source controller being configured to control the light source so as to illuminate at least a portion of the light passing wall of the housing with the light generated by the light source, the light source being dedicated to illuminating the light passing wall, and

wherein the housing further includes one or more opaque walls that cooperate with the one or more light passing walls to define the shape of the housing.

52. (Cancelled)

53. (Cancelled)

54. (Cancelled)

55. (Cancelled)

56. (Previously Presented) A general purpose computer, comprising:

a housing including one or more walls that define the outer peripheral form of the general purpose computer, one of the walls having an illuminable portion configured to allow the passage of light therein;

a controllable light emitting device enclosed by the housing, the light emitting device being configured to produce an adjustable light effect for colorizing or patternizing the illuminable portion; and

a processor enclosed by the housing, the processor being configured to at least partially control the operations of the general purpose computer.

57. (Original) The general purpose computer as recited in claim 56 wherein the processor is coupled to the light emitting device and further configured to control the light emitting device so as to produce a light effect.

58. (Original) The general purpose computer as recited in claim 56 further including a second processor enclosed by the structural housing, the second processor being configured to control the light emitting device so as to produce a light effect.



**BEST AVAILABLE COPY**

59. (Original) The general purpose computer as recited in claim 56 wherein the illuminable portion constitutes a substantial portion of the entire housing.

60. (Original) The general purpose computer as recited in claim 59 wherein the illuminable portion constitutes the entire housing.

61. (Original) The general purpose computer as recited in claim 59 wherein the illuminable portion constitutes one or more walls of the housing.

62. (Original) The general purpose computer as recited in claim 59 wherein the illuminable portion constitutes a part of two or more walls of the housing.

63. (Original) The general purpose computer as recited in claim 59 wherein the illuminable portion constitutes a part of a wall of the housing.

64. (Original) The general purpose computer as recited in claim 56 wherein the area of the illuminable portion is substantially larger than any of buttons, connectors or indicators located on the housing.

65. (Currently Amended) A display for use with a general purpose computer, comprising  
a housing including one or more wall that define the outer peripheral form of the display,  
one of the walls having an illuminable portion configured to allow the passage of light therein;  
a controllable light arrangement enclosed by the housing and in optical communication  
with the illuminable portion, the light arrangement being configured to produce an adjustable  
light effect that provides illumination for colorizing or patternizing the illuminable portion; and  
a display screen partially enclosed by the housing, the display screen being configured to  
display text or graphics via a graphical user interface.

66. (Previously Presented) A computing device comprising an enclosure having an  
illuminable wall in optical communication with a light source disposed inside the enclosure, and  
a control means for varying a characteristic or attribute of the light generated by the light source,  
said illuminable wall and said light source working together to emit a characteristic glow at a  
peripheral portion of said enclosure, wherein the illuminable wall helps to structurally support

**BEST AVAILABLE COPY**

the internal components of the computing device in their assembled position within the enclosure and wherein the illuminable wall is formed from a translucent or semi translucent material.

67. (Original) The computing device as recited in claim 66 wherein the enclosure defines the outer peripheral form of the computing device.

68. (Cancelled)

69. (Original) The computing device as recited in claim 66 wherein the illuminable wall includes a light directing element configured to scatter light from the light source, the scattered light helping to form the characteristic glow.

70. (Previously Presented) A computing device comprising an enclosure having an illuminable wall in optical communication with a light source disposed inside the enclosure, and a control means for varying a characteristic or attribute of the light generated by the light source, said illuminable wall and said light source working together to emit a characteristic glow at a peripheral portion of said enclosure, the illuminable wall including a light directing element configured to scatter light from the light source, the scattered light helping to form the characteristic glow, wherein the light directing element is an additive disposed inside the illuminable wall.

71. (Previously Presented) A computing device comprising an enclosure having an illuminable wall in optical communication with a light source disposed inside the enclosure, and a control means for varying a characteristic or attribute of the light generated by the light source, said illuminable wall and said light source working together to emit a characteristic glow at a peripheral portion of said enclosure, the illuminable wall including a light directing element configured to scatter light from the light source, the scattered light helping to form the characteristic glow, wherein the light directing element is a coating applied to the illuminable wall.

72. (Previously Presented) A computing device comprising an enclosure having an illuminable wall in optical communication with a light source disposed inside the enclosure, and a control means for varying a characteristic or attribute of the light generated by the light source, said illuminable wall and said light source working together to emit a characteristic glow at a

**BEST AVAILABLE COPY**

peripheral portion of said enclosure, the illuminable wall including a light directing element configured to scatter light from the light source, the scattered light helping to form the characteristic glow, wherein the light directing element is a textured surface of the illuminable wall.

73. (Original) The computing device as recited in claim 66 wherein the characteristic glow is formed at an outer surface of the illuminable wall.

74. (Original) The computing device as recited in claim 66 the characteristic glow is formed at an outer edge of the illuminable wall.

75. (Cancelled)

76. (Cancelled)

77. (Cancelled)